

## N Series Gas Instruments

Designed for today, prepared for tomorrow



#### Who we are


- Kirk Lovewell VP of Engineering
  - 31 years with TAPI, developing AQMS analyser and calibrator products, leading engineering teams
- France Meder VP of Global Sales and Marketing
  - 10 years with TAPI, product management, service management


#### T-Series to N-Series Transition

- All common CEMS models now available in N-Series.
- T-Series will remain in full-production likely through 2026.
- Support for T-Series (spare part sales and in-house repairs) will extend for 10 years after last production (subject to material availability).

# N Series Highlights

- Smart Internal Hardware Modules
  - Easy field replacement with pre-calibrated and tested modules
- CAN Bus Communications Architecture
  - Simplified, common cabling increases reliability
- 24VDC Internal Power
  - Lower power consumption and unified power requirement
  - Ability to easily operate from alternative power source
  - No AC voltage switch only external pumps are voltage dependent
- Split Fold-down Rear Panel
  - Access to pneumatic connections inside bulkhead
- NumaView<sup>TM</sup> Software Interface
  - Familiar, mature, and customizable with real-time graphing, diagnostic alerts, and preventative maintenance capabilities





### N Series Front Panel



- Standard 19" rack mountable chassis
- Optional ears, handles, and/or slides
- Capacitive, color touch-screen display
- 2 front-panel USB ports
- Soft power switch, allows for more reliable shut-down of system.




## N Series Rear Panel




- Split fold-down rear panel
- Robust pneumatic bulkhead fittings
- Ethernet and serial communications with Modbus protocol
- Analog output and Digital expansion cards (optional)




## N Series Wiring Architecture




- Single, universal power supply
- Power and data provided in a single cable set
- All CAN Bus cables and connectors are common
- CAN bus is a robust multidrop, half-duplex, differential, industrial protocol.
- Simplified cabling and connections = improved reliability!!



## N Series PCBAs and Firmware




## N Series CANBUS Cable






CN53 PHYSICAL PINOUT WIRE SIDE VIEW



#### Common Smart Modules

- Mainboard Module
  - Serves as the "carrier board" for the CPU
  - Provides the core set of user-accessible I/O, including Ethernet and Serial ports
  - DC power distribution and CAN bus hub
  - Provides all power management including soft power switch




#### Communication Modules

- Digital I/O expansion
  - Status out, control in, alarm relays
- Analog outputs
  - 3 x current (4-20 mA)
  - 4 x voltage (5 or 10V)

## Firmware updates


- N Series firmware updates both the NVS and the PCBAs
- The PCBA firmware is embedded in the NVS update
- 1. Encrypted NVS firmware is copied into the /Upgrade folder on the /Hard Disk
- Instrument is rebooted. NVS upgrade file is unpacked. NVS firmware is updated.
- Tags get merged as needed.
- 4. Instrument boots to new NVS version.
- 5. Instrument checks PCBA firmware version against /Hard Disk/Firmware. If /Hard Disk is newer than board firmware, the CPU "bootloads" the PCBA. This occurs one at a time for each board present. The updated can't "downgrade" PCBA firmware.


## PCBA Bootloading



/Hard Disk/Firmware/		
Name	Size	Changed
<b>1</b>		
08791_1_11_1_1.hex	221 KB	3/24/2023 11:49 AM
08899_1_11_1_9_4.hex	162 KB	9/19/2023 2:43 PM
09173_1_11_1_1.hex	101 KB	8/31/2023 3:41 PM
09184_1_11_1_0_1.hex	69 KB	6/6/2022 1:43 PM
09187_1_11_1_1.hex	126 KB	3/24/2023 11:49 AM
09260_1_11_1_5_1.hex	282 KB	9/15/2023 9:46 AM
09269_1_11_1_0_1.hex	114 KB	6/6/2022 1:43 PM
09349_1_11_1_0_1.hex	81 KB	6/6/2022 1:43 PM
09366_1_11_1_0_2.hex	240 KB	6/26/2023 12:14 PM
09453_1_11_1_2_1.hex	169 KB	6/29/2022 2:03 PM
09542_1_11_1_3_1.hex	128 KB	12/6/2022 5:19 PM
09730_1_11_1_3_0.hex	132 KB	8/31/2023 3:41 PM









Rcell Pressure

Sample Pressure

#### Measurement and Control


- All measurement and control occurs at the module
- Temperature measurement and control
- PMT HVPS and measurement
- Valve drivers
- Pressure measurements
- "Finished Data" is sent over 2wire CAN BUS to Mainboard and CPU/SOM





# Tags – What are they?

- NumaView uses "Tags" to store data
- Tags can be constants or changing values
- Tags can be read-only or read-write
- Some diagnostic tags can be displayed on the Dashboard or as meters
- Provide insight into the operation of the machine
- Located in /Hard Disk/Configuration as tags\_A.xml and tags\_B.xml



# Reading Tags – REST Protocol

- <a href="http://10.0.1.149:8180/api/taglist">http://10.0.1.149:8180/api/taglist</a> will dump all tags and values to a text file (with no extension).
- Chrome works well for grabbing the full taglist using the URL above
- Rename the file taglistXX.txt and open with a text editor
- Individual tags can be read with

taglist (9).txt - Notepad

File Edit Format View Help

\"IsDashboard\":false,\"CanDashboard\":false}"},{"name":"SV\_03\_SLOPE","type":"float","value":"0.981924295425415","properties":"{\"Precision\":3, \":1.0,\"Name\":\"SV\_03\_SLOPE\",\"HmiLabel\":\"Photo Slope\",\"Description\":\"03 Photometer Calibration Slope\",\"Group\":\"CFG,LOG\",\"Units\" \"IsNonVolatile\":true,\"IsDashboard\":true,\"CanDashboard\":true}"},{"name":"SV\_03\_0FFSET","type":"float","value":"-0.515456974506378","propert \"EuTag\":\"\,"Default\":0.0,\"Name\":\"SV 03 OFFSET\",\"HmiLabel\":\"Photo Offset\",\"Description\":\"03 Photometer Calibration Offset\",\"Gr \":true,\"IsVisible\":true,\"IsNonVolatile\":true,\"IsDashboard\":true,\"CanDashboard\":true}"},{"name":"SV\_03\_SLOPE\_CONSTANT","type":"float","v \"EuMax\":10.0,\"EuTag\":\"",\"Default\":1.0,\"Name\":\"SV\_03\_SLOPE\_CONSTANT\",\"HmiLabel\":\"SV\_03\_SLOPE\_CONSTANT\",\"Description\":\"03 calib \"IsValueValid\":true,\"IsReadOnly\":false,\"IsNetwork\":true,\"IsVisible\":true,\"IsNonVolatile\\":false,\"IsDashboard\":false,\"CanDashboard\": {"name":"SV\_03\_TARGET\_SPAN\_CONC","type":"float","value":"400","properties":"{\"Precision\":1,\"RawMin\":0.1,\"RawMax\":2000000000.0,\"EuMin\":0. \",\"HmiLabel\":\"SV\_03\_TARGET\_SPAN\_CONC\",\"Description\":\"Bench Cal Target 03 Gen Conc\",\"Group\":\"CLONE\",\"Units\":\"PPB\",\"IsValueValid \"IsDashboard\":false,\"CanDashboard\":false}"},{"name":"SV\_03\_GEN\_FLOW","type":"float","value":"0.133","properties":"{\"Precision\":3,\"RawMin\ \":\"SV\_03\_GEN\_FLOW\",\"HmiLabel\":\"Nominal 03 Gen Flow\",\"Description\":\"Nominal 03 generator flow rate\",\"Group\":\"CFG1,CLONE\",\"Units\" \"IsNonVolatile\":true,\"IsDashboard\":false,\"CanDashboard\":false}"},{"name":"SV\_O3\_BENCH\_DELAY","type":"float","value":"120","properties":"{\ \"Default\":120.0,\"Name\":\"SV 03 BENCH DELAY\",\"HmiLabel\":\"SV BENCH DELAY\",\"Description\":\"Bench feedback control delay\",\"Group\":\"CF \"IsVisible\":true,\"IsNonVolatile\":false,\"IsDashboard\":false,\"CanDashboard\":false}\"},\"name":"SV\_O3\_BENCH\_ADJUSTMENT\_FREQUENCY", "type":"fl \":1.0,\"EuMax\":1000.0,\"EuTag\":\"\,\"Default\":10.0,\"Name\":\"SV\_03\_BENCH\_ADJUSTMENT\_FREQUENCY\",\"HmiLabel\":\"SV\_03\_BENCH\_ADJUSTMENT\_FREQUENCY\",\"SV\_03\_BENCH\_ADJUSTMENT\_FREQUENCY\",\"SV\_03\_BENCH\_ADJUSTMENT\_FREQUENCY\",\"HmiLabel\":\"SV\_03\_ \"Seconds\",\"IsValueValid\":true,\"IsReadOnly\":false,\"IsNetwork\":true,\"IsVisible\":true,\"IsNonVolatile\":false,\"IsDashboard\":false,\"Can {"name":"SV 03 BENCH FILTER SIZE","type":"int","value":"3","properties":"{\"RawMin\":1,\"RawMax\":10,\"EuMin\":1,\"EuMax\":1000,\"EuTag\":\"\",\ \"Description\":\"03 bench mode filter size\",\"Group\":\"CFG1\",\"Units\":\"Samples\",\"IsValueValid\":true,\"IsReadOnly\":false,\"IsNetwork\": \":false}"},{"name": "SV\_03\_CACHE\_UPDATE\_STABILITY\_LIMIT", "type": "float", "value": "10", "properties": "{\"Precision\":3,\"RawMin\":0.1,\"RawMax\":10 \"SV 03 CACHE UPDATE STABILITY LIMIT\",\"HmiLabel\":\"SV 03 CACHE UPDATE STABILITY LIMIT\",\"Description\":\"Drive stability limit for concentra \":false,\"IsNetwork\":true,\"IsVisible\":true,\"IsNonVolatile\":false,\"IsDashboard\":false,\"CanDashboard\":false}"},{"name":"SV\_03\_BENCH\_PID\_ \"RawMax\":10.0,\"EuMin\":0.0,\"EuMax\":100.0,\"EuTag\":\"\,\"Default\":0.2,\"Name\":\"SV 03 BENCH PID INTEGRAL\",\"HmiLabel\":\"SV 03 BENCH PI \"CFG1,CLONE\",\"Units\":\"Gain\",\"IsValueValid\":true,\"IsReadOnly\":false,\"IsNetwork\":false,\"IsVisible\":false,\"IsNonVolatile\":true,\"Is {"name":"SV\_03\_BENCH\_PID\_DERIVATIVE","type":"float","value":"0.5","properties":"{\"Precision\":3,\"RawMin\":0.0,\"RawMax\":10.0,\"EuMin\":0.0,\" \"HmiLabel\":\"SV\_03\_BENCH\_PID\_DERIVATIVE\",\"Description\":\"03 bench mode PID derivative coefficient\",\"Group\":\"CFG1,CLONE\",\"Units\":\"Ga \"IsNonVolatile\":true,\"IsDashboard\":false,\"CanDashboard\":false\"} { "name":"SV PHOTO ZERO READING", "type":"float", "value":"0.524945735931396 \"EuMax\":1000.0,\"EuTag\":\"\",\"Default\":0.0,\"Name\":\"SV\_PHOTO\_ZERO\_READING\",\"Description\":\"Photo\_ZERO\_READING\",\"Description\":\"Descriptio \"PPB\",\"IsValueValid\":true,\"IsReadOnly\":false,\"IsNetwork\":false,\"IsVisible\":false,\"IsNonVolatile\":true,\"IsDashboard\":false,\"CanDas ".amme":"SV\_PHOTO\_ZERO\_ACTUAL","type":"float","value":"0","properties":"{\"Precision\":1,\"RawMin\":-100.0,\"RawMax\":100.0,\"EuMin\":-1000.0,\" \":\"SV PHOTO ZERO ACTUAL\",\"Description\":\"Actual 03 concentration at most recent photometer zero calibration\",\"Group\":\"SYSTEM,CLONE\",\"

- http://10.0.1.149:8180/api/tag/SV\_O3\_SLOPE
- {"name":"SV\_O3\_SLOPE","type":"float","value":"0.981924295425415","properties":"{\"Precisi on\":3,\"RawMin\":0.85,\"RawMax\":1.15,\"EuMin\":0.85,\"EuMax\":1.15,\"EuTag\":\"\",\"Defa ult\":1.0,\"Name\":\"SV\_O3\_SLOPE\",\"HmiLabel\":\"Photo Slope\",\"Description\":\"O3 Photometer Calibration
  - Slope\",\"Group\":\"CFG,LOG\",\"Units\":\"\",\"IsValueValid\":true,\"IsReadOnly\":false,\"IsNet work\":true,\"IsVisible\":true,\"IsNonVolatile\":true,\"IsDashboard\":true,\"CanDashboard\":true}"}



Teledyne Confidential

# Internal Layout (N200M)

Split fold-down rear panel

Sensor smart module

Optional integrated paramagnetic O2 sensor

Ozone generator smart module


Common electronics with a single 24VDC power supply



# Internal Layout (N300)

\*options available on ambient models

Internal Zero/Span Valve Assy\*




Flow system smart module with Pulse-width modulated (PWM) control

Long-life or 47mm sample filter holders\*




# Sample Filter Options


Traditional 47mm



New Long-Life Filter (DFU)




#### N100 Pneumatics



- Optional O2 Sensor
- Optional
   Calibration Valves
- Optional permeation calibration source


# N100 Layout

Each module connects to main board via common CAN, 24V, 5VDC cable




#### N100 Sensor Module

- Sensor calibration stored on module
- Similar optics and spare parts as T Series (aside from PCBAs)
- No Shutter in N Series
- No PMT potentiometers




## N100 PMT and TEC






## N100/N200 PMT Adjust Screen

- Software driven HVPS adjustments allows for remote calibration
- Maintenance Mode can be logged in internal DAS
- Allows calibration w/o removing analyzer cover
- Other Utilities >
   Diagnostics familiar to
   T Series




## Dashboard / Diagnostics

- Tag units may differ from E and T series
- Acceptance ranges for tags may be found in respective user's manuals
- Many signal voltages no longer normalized to 5000mV scale




# MCU Recovery App

- Each N Series module operates with its own firmware and communicates data over CAN Bus.
- MCU Recovery app deals with issues if firmware updates get interrupted.
- Work with TAPI technical support to use this feature



### NumaView<sup>TM</sup> Software Interface

Customizable, content rich, and intuitive user interface



User-definable meter variables



### NVS – Home Screen


Real-time graphical representation of concentration and stability






# NVS - Dashboard User Config

Fully configurable dashboard









#### NVS - Dashboard Real-Time Plots

Real-time graphical representation of test functions



#### NVS – Alerts


Simultaneous display of all active alerts with time stamp and cause





## NVS – Custom Alerts and Alarms


Custom events and warnings






## **NVS - Calibrations**

#### Simple Calibrations



## NVS - Data Acquisition


Triggers for data logging, including periodic and conditional






# **NVS Data Viewing**

Customizable datasets that can be viewed on the GUI



# NVS - Full USB Support


Data Upload and Download





# NVS - Digital Output Config


Easily map data 'tags' to any digital output channel





# NVS - Analog Output Config

Easily map any data 'tags' to any analog output





# Tech Support

- TAPI has a re-vamped tech support team
  - Retirement of several very experience techs, training several new hires.
  - New management structure, implementing best-practices.
- Tech Support Tips
  - For performance issues, download and send instrument DAS data (HIRES logger) when making initial contact.
  - Custom data loggers can be easily added, but please do not alter the default HIRES logger, this
    data is selected for tech support diagnosis.

## Teledyne API N Series Gas Analyzers



Designed for today, prepared for tomorrow

Thank you for your attention! Questions???







www.teledyne-api.com



Teledyne API



linkedin.com/company/tapi

